

SIRIUS
RFID Antenna
Industry

PART ID:
4741

The SIRIUS 4741 Antenna is a compact RFID UHF antenna with a very high gain, circular polarization, and radiation pattern characterized by a wide beam in all directions in one hemisphere. The SIRIUS 4741 is also available without enclosure.

Main Specifications

Frequencies	LF HF UHF
Material	ABS+PC
Operating Temperature	-20°C to 60°C
IP Class	IP67
Compliance	RoHs & REACH, FCC, CE
Key Features	Rough Environment, High gain, Wide beam, Compact Design



Full Specifications

Product ID	4741
Name	SIRIUS
Material	ABS+PC
Shape	Long Range
Long Description	The SIRIUS 4741 Antenna is a compact RFID UHF antenna with a very high gain, circular polarization, and radiation pattern characterized by a wide beam in all directions in one hemisphere. The SIRIUS 4741 is also available without enclosure.
Key Features	Rough Environment, High gain, Wide beam, Compact Design
Main Use	Industrial Application
Article Type	Industry
Color	white
Length [mm]	270
Width [mm]	270
Thickness [mm]	79
Weight [g]	1260
IP Class	IP67
PCB Material	ABS
Chemical Resistance	Not Specified

®TECTUS reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. TECTUS declines all responsibility for the use of products with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility. Where application information is given, it is only advisory and does not form part of the specification.

Flame Resistance	Not Specified
Mechanical Resistance	IEC 68.2.27/ IEC 68.2.6
Compliance	RoHs & REACH, FCC, CE
Operating Temp °C (min)	-20
Operating Temp °C (max)	60
Storage Temp °C (min)	-20
Storage Temp °C (max)	60
Peak Temp I / °C	80
Typical Reading Range	up to 12m
Operating Frequency	UHF
Frequency Range	865 - 868 MHz
Impedance [Ohm]	50 Ohm
Mounting Method	Pole/Wall

VARIANTS

ID	Variant
4741-01-000-00	internal SMA

®TECTUS reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. TECTUS declines all responsibility for the use of products with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility. Where application information is given, it is only advisory and does not form part of the specification.