

Transponder

ISO Card

PART ID:
1055-01-349-00

These cards combine innovative printing and radio frequency identification (RFID) technologies with industry-leading knowledge in the production of secure identity components and solutions. Proven processes and automated manufacturing ensure efficient and cost-effective production of high quality cards. ISO cards are used in billions around the world, ranging from simple, non-technology printed loyalty cards to highly secure access control, payment or citizen ID cards. ISO 7816 Compliant

Main Specifications

| | |
|-----------------------|---|
| Material | PVC+PETF |
| Operating Temperature | -35°C to 70°C |
| IP Class | IP68 |
| Compliance | RoHs & Reach, CE |
| Key Features | High Quality Card, High-Resolution Print, Cost-Effective, Heat Tolerant |
| Options | Laser Engraving, Logo, UID Printing, Dual Frequency On Request |



Chip Specification (Chip 349)

| | |
|-----------|--------------------------------------|
| Chip | Alien - Higgs 3 |
| Frequency | 869 MHz (UHF) |
| Memory | TID 64 Bit; EPC 96 Bit; User 512 Bit |
| Norm | ISO 18000-6C / EPC Gen2 V2 |

Full Specifications

| | |
|------------------|--|
| Product ID | 1055 |
| Material | PVC+PETF |
| Shape | Laminated |
| Long Description | These cards combine innovative printing and radio frequency identification (RFID) technologies with industry-leading knowledge in the production of secure identity components and solutions. Proven processes and automated manufacturing ensure efficient and cost-effective production of high quality cards. ISO cards are used in billions around the world, ranging from simple, non-technology printed loyalty cards to highly secure access control, payment or citizen ID cards. ISO 7816 Compliant |

®TECTUS reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. TECTUS declines all responsibility for the use of products with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility. Where application information is given, it is only advisory and does not form part of the specification.

| | |
|-------------------------|--|
| Key Features | High Quality Card, High-Resolution Print, Cost-Effective, Heat Tolerant |
| Options | Laser Engraving, Logo, UID Printing, Dual Frequency On Request |
| Comments | Magnet Stripes: HiCo: 2750o.e. / 4000o.e. (3600o.e.) LoCo: 300o.e. / 650o.e. |
| Main Use | Access Control |
| Article Type | ISO Card |
| Color | White |
| Length [mm] | 85.6 |
| Width [mm] | 54 |
| Thickness [mm] | 0.8 |
| Weight [g] | 6 |
| Operating Temp °C (min) | -35 |
| Operating Temp °C (max) | 70 |
| Storage Temp °C (min) | -40 |
| Storage Temp °C (max) | 100 |
| IP Class | IP68 |
| Chemical Resistance | Not Specified |
| Flame Resistance | Not Specified |
| Mechanical Resistance | Not Specified |
| Attachment Method | Card Holder |
| Compliance | RoHs & Reach, CE |

VARIANTS AND ICS

| ID | Variant | Band | Type | ISO |
|----------------|----------|------|-----------------------|-----------------------------|
| 1055-01-152-00 | ISO Card | LF | EM4200/Unique | ISO/IEC 11784/85 Compatible |
| 1055-01-206-00 | ISO Card | HF | MIFARE Classic EV1 1K | ISO/IEC 14443A & 18000-3 |
| 1055-01-260-00 | ISO Card | HF | ICODE SLIX | ISO/IEC 15693 & 18000-3 |
| 1055-01-349-00 | ISO Card | UHF | Higgs 3 | ISO 18000-6C / EPC Gen2 V2 |