

Transponder ON METAL

Label

PART ID:
2023

90x28 On Metal Label provides excellent performance and long reading range up to 4 meters. Its performance goes well on metallic objects for various applications.

Main Specifications

Frequencies	LF HF UHF
Material	PP
Operating Temperature	-40°C to 85°C
IP Class	IP68
Compliance	RoHs & Reach, CE
Key Features	Ultra Thin, ON-Metal Use, Cost-Effective
Options	Adhesive, Preprinted Artwork, Logo, Barcode



Full Specifications

Product ID	2023
On Metal Use	yes
Material	PP
Shape	Label structure square
Long Description	90x28 On Metal Label provides excellent performance and long reading range up to 4 meters. Its performance goes well on metallic objects for various applications.
Key Features	Ultra Thin, ON-Metal Use, Cost-Effective
Options	Adhesive, Preprinted Artwork, Logo, Barcode
Article Type	Label
Color	White
Length [mm]	90
Width [mm]	28
Thickness [mm]	0.8
Weight [g]	3
Operating Temp °C (min)	-40
Operating Temp °C (max)	85
Storage Temp °C (min)	-40
Storage Temp °C (max)	85
IP Class	IP68

©TECTUS reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. TECTUS declines all responsibility for the use of products with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility.

Where application information is given, it is only advisory and does not form part of the specification.

Chemical Resistance	Not Specified
Flame Resistance	Not Specified
Mechanical Resistance	Not Specified
Attachment Method	Sticker
Compliance	RoHs & Reach, CE

VARIANTS AND ICS

ID	Variant	Band	Type	ISO
2023-01-362-00	90x28x0.9mm	UHF	Monza 4QT	ISO 18000-6C / EPC Gen2 V2