

Transponder

DISC TAG

PART ID:

1006-02-260-00

GF Stick Tag can be put on non-metallic surface for tracking, data recording or regular patrol purpose.

Main Specifications

| | |
|-----------------------|-------------------------------|
| Material | GF |
| Operating Temperature | -40°C to 85°C |
| IP Class | IP67 |
| Compliance | RoHs & Reach, CE |
| Key Features | Asset Tracking, Tool Tracking |
| Options | Laser Engraving, Offset Print |



Chip Specification (Chip 260)

| | |
|-----------|---------------------------|
| Chip | NXP - ICODE SLIX |
| Frequency | 13.56 MHz (HF) |
| Memory | UID 8 Byte; User 1024 Bit |
| Norm | ISO/IEC 15693 & 18000-3 |

Full Specifications

| | |
|-------------------------|---|
| Product ID | 1006 |
| Material | GF |
| Shape | Laminated |
| Short Description | GF Stick Tag can be put on non-metallic surface for tracking, data recording or regular patrol purpose. |
| Key Features | Asset Tracking, Tool Tracking |
| Options | Laser Engraving, Offset Print |
| Comments | Hole 3/3.2/4.3mm |
| Main Use | Asset Management, Process Control |
| Article Type | DISC TAG |
| Color | Black |
| Thickness [mm] | 1.6 |
| Hole | yes |
| Operating Temp °C (min) | -40 |
| Operating Temp °C (max) | 85 |
| Storage Temp °C (min) | -25 |

®TECTUS reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. TECTUS declines all responsibility for the use of products with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility.

Where application information is given, it is only advisory and does not form part of the specification.

| | |
|-----------------------|------------------|
| Storage Temp °C (max) | 120 |
| IP Class | IP67 |
| Chemical Resistance | Not Specified |
| Flame Resistance | Not Specified |
| Mechanical Resistance | Not Specified |
| Attachment Method | Screw/Rivet |
| Compliance | RoHs & Reach, CE |

VARIANTS AND ICS

| ID | Variant | Band | Type | ISO |
|----------------|----------------------|------|---------------|-----------------------------|
| 1006-02-152-00 | D30x1.6mm Hole 3.2mm | LF | EM4200/Unique | ISO/IEC 11784/85 Compatible |
| 1006-02-260-00 | D30x1.6mm Hole 3.2mm | HF | ICODE SLIX | ISO/IEC 15693 & 18000-3 |
| 1006-03-152-00 | D50x1.6mm Hole 4.3mm | LF | EM4200/Unique | ISO/IEC 11784/85 Compatible |
| 1006-04-260-00 | D50x1.6mm Hole 3mm | HF | ICODE SLIX | ISO/IEC 15693 & 18000-3 |