

Transponder

DISC TAG

PART ID:

1007

GF Disc Tag can be put on non-metallic surface for tracking, data recording or regular patrol purpose.

Main Specifications

| | |
|-----------------------|-------------------------------|
| Frequencies | LF HF UHF |
| Material | GF |
| Operating Temperature | -40°C to 85°C |
| IP Class | IP67 |
| Compliance | RoHs & Reach, CE |
| Key Features | Tool Tracking, Asset Tracking |
| Options | Laser Engraving, Offset Print |



Full Specifications

| | |
|-------------------------|--|
| Product ID | 1007 |
| Material | GF |
| Shape | Laminated |
| Short Description | GF Disc Tag can be put on non-metallic surface for tracking, data recording or regular patrol purpose. |
| Long Description | GF Disc Tag can be put on non-metallic surface for tracking, data recording or regular patrol purpose. |
| Key Features | Tool Tracking, Asset Tracking |
| Options | Laser Engraving, Offset Print |
| Main Use | Asset Management, Process Control |
| Article Type | DISC TAG |
| Thickness [mm] | 1.6 |
| Operating Temp °C (min) | -40 |
| Operating Temp °C (max) | 85 |
| Storage Temp °C (min) | -25 |
| Storage Temp °C (max) | 120 |
| IP Class | IP67 |
| Chemical Resistance | Not Specified |
| Flame Resistance | Not Specified |
| Mechanical Resistance | Not Specified |

©TECTUS reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. TECTUS declines all responsibility for the use of products with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility. Where application information is given, it is only advisory and does not form part of the specification.

| | |
|-------------------|------------------|
| Attachment Method | Glue |
| Compliance | RoHs & Reach, CE |

VARIANTS AND ICS

| ID | Variant | Band | Type | ISO |
|----------------|-----------|------|---------------|-----------------------------|
| 1007-01-152-00 | D20x1.6mm | LF | EM4200/Unique | ISO/IEC 11784/85 Compatible |
| 1007-02-152-00 | D25x1.6mm | LF | EM4200/Unique | ISO/IEC 11784/85 Compatible |
| 1007-03-152-00 | D30x1.6mm | LF | EM4200/Unique | ISO/IEC 11784/85 Compatible |
| 1007-04-152-00 | D50x1.6mm | LF | EM4200/Unique | ISO/IEC 11784/85 Compatible |