

Transponder ON METAL

DISC TAG

PART ID:
2019-01-264-00

Versatile disc-shaped RFID tags designed to perform in the toughest conditions.

Main Specifications

Material	PPA
Operating Temperature	-40°C to 85°C
IP Class	IP69K
Compliance	RoHs & Reach, CE
Key Features	Rough Environment, ON-Metal Use, Heat Tolerant
Options	Pad Printing



Chip Specification (Chip 264)

Chip	NXP - ICODE SLIX 2
Frequency	13.56 MHz (HF)
Memory	UID 8 Byte; User 2528 Bit
Norm	ISO/IEC 15693 & 18000-3

Full Specifications

Product ID	2019
On Metal Use	yes
Material	PPA
Shape	Overmolded
Short Description	Versatile disc-shaped RFID tags designed to perform in the toughest conditions.
Long Description	passive contactless RFID transponders are highly ruggedized and ideal for multiple industrial applications. The versatile heavy-duty tags offer a round disc shape makes them easy to fix with a single screw or rivet.
Key Features	Rough Environment, ON-Metal Use, Heat Tolerant
Options	Pad Printing
Comments	PEAK >120°C
Main Use	Manufacturing Automation
Article Type	DISC TAG
Color	Black
Diameter [mm]	50

®TECTUS reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. TECTUS declines all responsibility for the use of products with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility. Where application information is given, it is only advisory and does not form part of the specification.

Thickness [mm]	13
Weight [g]	30
Hole	yes
Operating Temp °C (min)	-40
Operating Temp °C (max)	85
Storage Temp °C (min)	-40
Storage Temp °C (max)	90
High Temp	yes
IP Class	IP69K
Chemical Resistance	Not Specified
Flame Resistance	UL 94 HB
Mechanical Resistance	Not Specified
Attachment Method	Screw/Rivet
Compliance	RoHs & Reach, CE

VARIANTS AND ICS

ID	Variant	Band	Type	ISO
2019-01-264-00	D50mm	HF	ICODE SLIX 2	ISO/IEC 15693 & 18000-3