

# Transponder ON METAL

## Square TAG

PART ID:

**2051-01-368-00**

Robust, RAIN® UHF tag designed to be welded on steel kegs to deliver long read ranges worldwide. Laser engraving with bar code and/or logo possible.

### Main Specifications

Material	Polyamid
Operating Temperature	-40°C to 85°C
IP Class	IP68
Compliance	RoHs & Reach, CE
Key Features	ON-Metal Use, Rough Environment, High Durability



### Chip Specification (Chip 368)

Chip	Impinj - Monza R6
Frequency	860~960 MHz ( UHF )
Memory	TID 48 Bit; EPC 96 Bit
Norm	ISO 18000-6C / EPC Gen2 V2

## Full Specifications

Product ID	2051
On Metal Use	yes
Material	Polyamid
Shape	Overmolded
Short Description	Robust, RAIN® UHF tag designed to be welded on steel kegs to deliver long read ranges worldwide. Laser engraving with bar code and/or logo possible.
Long Description	Square Tag transponders are the most advanced general-purpose RAIN® UHF tags available. Square Tag Curve is arched to hug metallic kegs or gas cylinders and durably withstands typical washing and disinfection cycles. The tags are lightweight, waterproof and resist high-pressure / high temperature washing conditions according to the highest standard (IP69K). Square Tag curved RFID tags include HID Global's patented 3D antenna, enabling omnidirectional read range performance independent of mounting material.
Key Features	ON-Metal Use, Rough Environment, High Durability
Main Use	Asset Tracking
Article Type	Square TAG
Color	Grey

Length [mm]	52
Width [mm]	26.5
Thickness [mm]	21.4
Weight [g]	20
Operating Temp °C (min)	-40
Operating Temp °C (max)	85
Storage Temp °C (min)	-40
Storage Temp °C (max)	85
IP Class	IP68
Chemical Resistance	Not Specified
Flame Resistance	Not Specified
Mechanical Resistance	IK 07
Attachment Method	Weld
Compliance	RoHs & Reach, CE

VARIANTS AND ICS

ID	Variant	Band	Type	ISO
2051-01-368-00	52x26.5x21.4mm, curved	UHF	Monza R6	ISO 18000-6C / EPC Gen2 V2

®TECTUS reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. TECTUS declines all responsibility for the use of products with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility. Where application information is given, it is only advisory and does not form part of the specification.