

Transponder ON METAL

Square TAG

PART ID:

2057-01-324-00

RAIN RFID PID 2057 (powered by NXP UCode 8 technology) can fit into small space while providing superior reading performance when compared to other tag in terms of size. It helps realize applications where other metal tags see a challenge. Built with TECTUS unique antenna design, this tag can avoid the interference caused by a dense metal environment as well.

Main Specifications

Material	Nylon Polymer
Operating Temperature	-40°C to 85°C
IP Class	IP68
Compliance	RoHs & Reach, CE, Rain RFID
Key Features	ON-Metal Use, Rough Environment, High Durability
Options	Laser Engraving



Chip Specification (Chip 324)

Chip	NXP - UCODE 8
Frequency	860~960MHz (UHF)
Memory	TID 96 Bit; EPC 128 Bit
Norm	ISO 18000-6C / EPC Gen2 V2

Full Specifications

Product ID	2057
On Metal Use	yes
Material	Nylon Polymer
Shape	Overmolded
Long Description	RAIN RFID PID 2057 (powered by NXP UCode 8 technology) can fit into small space while providing superior reading performance when compared to other tag in terms of size. It helps realize applications where other metal tags see a challenge. Built with TECTUS unique antenna design, this tag can avoid the interference caused by a dense metal environment as well.
Key Features	ON-Metal Use, Rough Environment, High Durability
Options	Laser Engraving
Article Type	Square TAG
Color	Black

©TECTUS reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. TECTUS declines all responsibility for the use of products with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility.

Where application information is given, it is only advisory and does not form part of the specification.

Length [mm]	50
Width [mm]	25
Thickness [mm]	6
Operating Temp °C (min)	-40
Operating Temp °C (max)	85
Storage Temp °C (min)	-40
Storage Temp °C (max)	120
IP Class	IP68
Chemical Resistance	Not Specified
Flame Resistance	Not Specified
Mechanical Resistance	Not Specified
Attachment Method	Glue
Compliance	RoHs & Reach, CE, Rain RFID

VARIANTS AND ICS

ID	Variant	Band	Type	ISO
2057-01-324-00	Black	UHF	UCODE 8	ISO 18000-6C / EPC Gen2 V2