

Transponder ATEX

Brick/Rod TAG

PART ID:
3007

ATEX Zone 1 / 21 certified UHF Mount On Metal BRICK MINI RFID
TAG 32 x 13 x 5 mm

Main Specifications

Frequencies	LF HF UHF
Material	Nylon Polymer
Operating Temperature	-40°C to 60°C
IP Class	IP68
Compliance	RoHs & Reach, CE
Key Features	ON-Metal Use, Rough Environment, Heat Tolerant, High Durability, Small Size



Full Specifications

Product ID	3007
Atex	yes
On Metal Use	yes
Material	Nylon Polymer
Shape	Overmolded
Short Description	ATEX Zone 1 / 21 certified UHF Mount On Metal BRICK MINI RFID TAG 32 x 13 x 5 mm
Long Description	The ATEX Zone 1 / 21 certified UHF Mount On Metal BRICK MINI RFID TAG 32 x 13 x 5 mm was developed to mark equipment and devices which have metallic surface and is located in hazardous areas. Despite the small shape the ATEX UHF RFID TAG is readable from a good distance by using ATEX certified stationary and portable ATEX UHF RFID readers. System integrators and users benefit of the ATEX Zone 1 / 21 certified UHF Mount On Metal BRICK MINI RFID TAG on off- and onshore oil rigs, in refineries, in chemical plants and in other application areas
Key Features	ON-Metal Use, Rough Environment, Heat Tolerant, High Durability, Small Size
Article Type	Brick/Rod TAG
Color	Black
Length [mm]	31.7
Width [mm]	12.8
Thickness [mm]	4.97
Weight [g]	5
Operating Temp °C (min)	-40
Operating Temp °C (max)	60

©TECTUS reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. TECTUS declines all responsibility for the use of products with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility. Where application information is given, it is only advisory and does not form part of the specification.

Storage Temp °C (min)	-40
Storage Temp °C (max)	60
IP Class	IP68
Chemical Resistance	Not Specified
Flame Resistance	Not Specified
Mechanical Resistance	Not Specified
Attachment Method	Glue
Compliance	RoHs & Reach, CE

VARIANTS AND ICS

ID	Variant	Band	Type	ISO
3007-01-349-00	31.7x12.8x4.97mm	UHF	Higgs 3	ISO 18000-6C / EPC Gen2 V2

®TECTUS reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. TECTUS declines all responsibility for the use of products with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility. Where application information is given, it is only advisory and does not form part of the specification.