

# Transponder ATEX

## Button/Round TAG

### PART ID:

**3014-01-113-00**

The ATEX Zone 1 / 21 certified 90 mm TEC PU ON METAL RFID TAG is available as 125 kHz /134 kHz and HF 13,56 MHz version. By using the centre mounting hole the transponder can be permanently affixed at the Objekt which has to be identified by means of screw or rivet. The rounded surface of the TAG has the benefit if an object hits the TAG it will be slid away from the TAG. Suitable stationary and portable ATEX certified LF and portable HF RFID readers are available.



### Main Specifications

Material	PU
Operating Temperature	-45°C to 60°C
IP Class	IP68
Compliance	RoHs & Reach, CE
Key Features	ON-Metal Use, Rough Environment, Heat Tolerant, High Durability
Options	Offset Print

### Chip Specification (Chip 113)

Chip	NXP - HITAG S 2048
Frequency	125 kHz ( LF )
Memory	UID 4 Byte; User 2048 Bit
Norm	ISO/IEC 11784 & 11785 & 14223

### Full Specifications

Product ID	3014
Atex	yes
On Metal Use	yes
Material	PU
Shape	Potted
Long Description	The ATEX Zone 1 / 21 certified 90 mm TEC PU ON METAL RFID TAG is available as 125 kHz /134 kHz and HF 13,56 MHz version. By using the centre mounting hole the transponder can be permanently affixed at the Objekt which has to be identified by means of screw or rivet. The rounded surface of the TAG has the benefit if an object hits the TAG it will be slid away from the TAG. Suitable stationary and portable ATEX certified LF and portable HF RFID readers are available.

®TECTUS reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. TECTUS declines all responsibility for the use of products with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility.

Where application information is given, it is only advisory and does not form part of the specification.

Key Features	ON-Metal Use, Rough Environment, Heat Tolerant, High Durability
Options	Offset Print
Comments	Hole 6.2mm
Article Type	Button/Round TAG
Color	Black
Diameter [mm]	90
Thickness [mm]	25
Weight [g]	130
Hole	yes
Operating Temp °C (min)	-45
Operating Temp °C (max)	60
Storage Temp °C (min)	-45
Storage Temp °C (max)	60
IP Class	IP68
Chemical Resistance	Not Specified
Flame Resistance	Not Specified
Mechanical Resistance	Not Specified
Attachment Method	Screw/Rivet
Compliance	RoHs & Reach, CE

## VARIANTS AND ICS

ID	Variant	Band	Type	ISO
3014-01-152-00	90x25mm	LF	EM4200/Unique	ISO/IEC 11784/85 Compatible
3014-01-113-00	90x25mm	LF	HITAG S 2048	ISO/IEC 11784 & 11785 & 14223
3014-01-260-00	90x25mm	HF	ICODE SLIX	ISO/IEC 15693 & 18000-3