

Tear Shape

Transponder ATEX Keyfob

PART ID:
3032-02-260-00

Tear Keyfob is constructed of two different color ABS plastic housings. Logo or ID numbering can be put on both sides of the housing.

Main Specifications

| | |
|-----------------------|---|
| Material | ABS |
| Operating Temperature | -25°C to 55°C |
| IP Class | IP66 |
| Compliance | RoHs & Reach, CE |
| Options | Laser Engraving, Offset Print, Dual Frequency LF/HF |

Chip Specification (Chip 260)

| | |
|-----------|---------------------------|
| Chip | NXP - ICODE SLIX |
| Frequency | 13.56 MHz (HF) |
| Memory | UID 8 Byte; User 1024 Bit |
| Norm | ISO/IEC 15693 & 18000-3 |



Full Specifications

| | |
|-------------------|---|
| Product ID | 3032 |
| Name | Tear Shape |
| Atex | yes |
| Material | ABS |
| Shape | Ultrasonic Welded |
| Short Description | Tear Keyfob is constructed of two different color ABS plastic housings. Logo or ID numbering can be put on both sides of the housing. |
| Options | Laser Engraving, Offset Print, Dual Frequency LF/HF |
| Main Use | Access Control |
| Article Type | Keyfob |
| Length [mm] | 40 |

| | |
|-------------------------|------------------|
| Width [mm] | 31 |
| Thickness [mm] | 5 |
| Weight [g] | 4.5 |
| Operating Temp °C (min) | -25 |
| Operating Temp °C (max) | 55 |
| Storage Temp °C (min) | -25 |
| Storage Temp °C (max) | 60 |
| IP Class | IP66 |
| Chemical Resistance | Not Specified |
| Flame Resistance | Not Specified |
| Mechanical Resistance | Not Specified |
| Attachment Method | Key-Hanger |
| Compliance | RoHs & Reach, CE |

VARIANTS AND ICS

| ID | Variant | Band | Type | ISO |
|----------------|---------|------|---------------|-------------------------------|
| 3032-01-152-00 | Red | LF | EM4200/Unique | ISO/IEC 11784/85 Compatible |
| 3032-01-260-00 | Red | HF | ICODE SLIX | ISO/IEC 15693 & 18000-3 |
| 3032-02-152-00 | Green | LF | EM4200/Unique | ISO/IEC 11784/85 Compatible |
| 3032-02-260-00 | Green | HF | ICODE SLIX | ISO/IEC 15693 & 18000-3 |
| 3032-03-152-00 | Yellow | LF | EM4200/Unique | ISO/IEC 11784/85 Compatible |
| 3032-03-260-00 | Yellow | HF | ICODE SLIX | ISO/IEC 15693 & 18000-3 |
| 3032-04-152-00 | Blue | LF | EM4200/Unique | ISO/IEC 11784/85 Compatible |
| 3032-04-260-00 | Blue | HF | ICODE SLIX | ISO/IEC 15693 & 18000-3 |
| 3032-04-113-00 | Blue | LF | HITAG S 2048 | ISO/IEC 11784 & 11785 & 14223 |
| 3032-05-152-00 | Grey | LF | EM4200/Unique | ISO/IEC 11784/85 Compatible |
| 3032-05-260-00 | Grey | HF | ICODE SLIX | ISO/IEC 15693 & 18000-3 |
| 3032-06-152-00 | Black | LF | EM4200/Unique | ISO/IEC 11784/85 Compatible |
| 3032-06-260-00 | Black | HF | ICODE SLIX | ISO/IEC 15693 & 18000-3 |